

Scheda Tecnica DVR TECNOACCESSORI®
MODELLO TC-4CH 8MP-P

TECNO®
www.tecnoaccessori.net
Accessori

Feature:

- Support H.265+ encoding, ultra-low bitrates, compatible with H.265+ surroundings
- Support VGA, HDMI full HD output simultaneously
- Support ONVIF;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support web, VMS, center platform management software MYEYE,
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP),easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals
- Support coaxial audio bidirectional transmission
- Support intelligent analysis: Human detection,



Specification:

	Model	4CH 8MP-P
System	Main processor	NT98332
Interface	Preview	1/4/8/9
Video	Codec	H.265+
	Monitor quality	VGA(1080P at most);HDMI(4K at most)
	Preview ability	4*8M@15fps(6 in 1)/4*5M@20fps(6 in 1)/ 4*4M(6 in 1) /4*3M (6 in 1)/4*1080P(6 in 1) default 8M
	Encode ability	4*8M@9fps(6 in 1)/4*5M@16fps(6 in 1)/ 4*4M@21fps(6 in 1)/4*3M@25fps(6 in 1)/4*1080P(6 in 1) default 8M
	Decode ability	4*8M@9fps(6 in 1)/4*5M@16fps(6 in 1)/ 4*4M@21fps(6 in 1)/4*3M@25fps(6 in 1)/4*1080P(6 in 1) default 8M
	Multi-mode input	Analog: 4*8M hybrid: 4*8M (analog) +4*8M (network) network: 16*1080P;8*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Coaxial audio	Support coaxial audio bidirectional transmission
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	4ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A

	Audio I/O	1*in/1*out
	Alarm I/O	0*in/0*out
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 14TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃ , Humidity:10%—90% , Atm:86kpa—106kpa
	Dimension	135mm*70mm
	Weight	104g

Prodotto Importato e Distribuito dalla TECNOACCESSORI®

A causa dei continui aggiornamenti si potrebbero riscontrare differenze nei dati tecnici sopra elencati

