

SCHEDA TECNICA

NVR poe

TECNOACCESSORI®

Modello .TC-NVR-4K-POE-08

Descrizione:

- Supporta l'accesso di più dispositivi front-end intelligenti XM con funzione di rilevamento umano e rilevamento del volto.
- Richiede alimentazione della scheda di espansione POE esterna e connessione di rete.
- Supporta uscita HDMI4K, VGA 1080P HD;
- Supporta ONVIF; accesso a terze parti;
- Supporta web, CMS, software di gestione della piattaforma centrale MYEYE, fornisce sviluppo SDK;
- Supporta più tecnologie cloud, penetrazione della rete, informazioni di allarme inviate al telefono e altre funzioni;
- Supporta più servizi di rete (supporta DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, ricerche IP, Alarm Center, ecc.);
- Supporta l'accesso al protocollo GB28181 a piattaforme di terze parti.

	Model	TC-NVR-4K-POE-08
System	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/2/4/6/9/10
Video	Video input (IP)	10*4K
	Video compression	H.265A/H.265+(compatible H.265/H.264)
	Display quality	Max:4K
	Playback quality	4K/5M/4M/3M/1080P
	Decode	4K (1) /5M (1+1) /4M(2+1)/3M (2+2) /1080P (4+1)
	VR	Unsupport
	human shape / Face	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local payback	4K (1) /5M (1+1) /4M(2+1)/3M (2+2) /1080P (4+1)
	Search mode	Search by Time/Calendar/Event/Channel/Face
	Record storage	HDD、Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1 (3.5mm)
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
	USB interface	2*USB2.0 ports(one USB extension interface is reserved)
	HDD	1* SATA(Up to 14TB for each disk)
POE	Interface	8 independent 100 Mbps PoE network interfaces
	Max Power	Max 30W for single port Max 108W in total (13.5W for each)
	Supported Standard	IEEE 802.3at, IEEE 802.3af
General	ONVIF	Support
	Power supply	52V DC
	Power Consumption	<10W(Without HDD,only for NVR)
	Work environment	Temperature:0℃ — 55℃, Humidity:10%—90%RH, Atm:86kpa—106kp
	Dimension	255(L)*220(W)*42(H)mm
	Weight	A total of about 1.6kg